



HIGH PERFORMANCE Dry Chemical

**Manufactured and Tested to
ANSI/UL Standards**
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED

EXTRA FEATURES:

- ★ Superior Range (Vertical & Horizontal)
 - ★ High (240 PSI) Operating Pressure
 - ★ Choice of Chemicals
 - ABC Multi Purpose, Regular, Purple K
 - ★ Select *Fast Flow* for:
 - High Flow Rate
 - Fast Discharge
 - Quicker Knockdown
 - More Operator Protection
 - ★ Select Compliance Flow for:
 - Long Range
 - Highest U.L. Ratings
 - ★ Painted GALVANIZED DRAWN STEEL Cylinders
(The best corrosion protection available anywhere)
 - ★ Protective Rubber Foot Rings
 - ★ All Metal Valve Construction
 - ★ Gauge Guards
 - ★ Bar Coded and Bi-lingual Labels
- (Temperature Range -65°F to 120°F)**

Note: All extinguishers are USCG approved with bracket listed on UL label.

Stored Pressure



HIGH PERFORMANCE extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use and extreme environment applications. Economical - less initial cost, lower maintenance costs and greater reliability than cartridge operated extinguishers.

Available in 125 and 250 lb. Wheeled and Stationary extinguishers.

Hot dip galvanized USCG brackets available

12 YEAR WARRANTY

SPECIFICATIONS	HIGH PERFORMANCE - ABC, REGULAR, PURPLE K Dry Chemical														
Type	FAST FLOW									COMPLIANCE FLOW					
Agent	ABC			REGULAR			PURPLE K			ABC			PURPLE K		
Size & Capacity - lbs. (kg)	13.2 (6)	20 (9)	30 (13.6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)	13.2 (6)	20 (9)	30 (13.6)
Model Number	594	581	567	582	568	595	580	584	569	592	564	589	599	566	591
U/L Rating	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	20A:120B:C	20A:160B:C	80B:C	120B:C	160B:C
Shipping Wt. (lbs.)	31	42½	58	42½	58	31	42½	42½	58	31	42½	58	31	42½	58
Height (in.)	17½	24¾	26½	24¾	26½	17½	24¾	24¾	26½	17½	24¾	26½	17½	24¾	26½
Width (in.)	10½	10½	11	10½	11	10½	10½	10½	11	10½	10½	11	10½	10½	11
Depth (Diam. - in.)	7	7	8	7	8	7	7	7	8	7	7	8	7	7	8
Range (ft.)	40-50			40-50			40-50			40-50			40-50		
Discharge Rate (Ave.) (lbs./sec.)	.94	1.20	1.60	1.40	1.76	.94	1.44	2.00	1.88	.59	.65	.95	.61	.67	.81
Discharge Time (sec.)	15	18	21	15	17	15	15	10	16	22	30	34	22	29	34
Standard Bracket	Wall														