



Regular Dry Chemical

Manufactured and Tested to
ANSI/UL Standards
ISO-9001:2000/ISO-14001:2004 Certified
UL LISTED AND USCG APPROVED

- ★ Dependable Drawn Steel Cylinders
- ★ All Metal Valve Construction
- ★ Easy and more economical to maintain and service
- ★ Bar Coded and Bi-lingual Labels

(Temperature Range -65°F to 120°F)

Note: All extinguishers are USCG approved with bracket listed on UL label.

Stored Pressure



REGULAR extinguishers contain a siliconized sodium bicarbonate based dry chemical with free flowing and non-caking additives. Economical Class B & C protection with lower initial cost and recharging. This chemical smothers fires in flammable liquids and pressurized gases and will not conduct electricity back to the operator.

Available in Wheeled and Stationary extinguishers.

6 YEAR WARRANTY

SPECIFICATIONS	REGULAR Dry Chemical								
	ALUMINUM					BRASS, CHROME PLATED			
Size & Capacity (lbs.)	1	2½	5	5½	10 Tall	20	6	10 Tall	20
Application	Nozzle			Hose and Nozzle					
Model Number	A620T	B403 B403T	B409T	B453	B457	A412	B462	B447	408
U/L Rating	2B:C	10B:C	10B:C	40B:C	60B:C	120B:C	40B:C	60B:C	120B:C
Shipping Wt. (lbs.)	2½	5½	9¼	9½	18	38	13¾	19	39
Height (in.)	10	15½	15¼	15¼	20	23¼	16¼	20½	24
Width (in.)	3½	5¾	5½	7¼	7¾	10¼	8½	8¾	10¼
Depth (Diam. - in.)	2¾	3	4¼	4¼	5	7	5	5	7
Range (ft.)	5 - 8	9 - 15	12 - 18	12 - 18	15 - 21	15 - 21	15 - 21	15 - 21	15 - 21
Discharge Time (Sec.)	10	10	10	14	18	28	14	18	28
Available with Chrome Plated Cylinder	Yes	Yes	Yes	Yes	Yes				
F. M. Approved		Yes	Yes		Yes	Yes	Yes	Yes	Yes
Standard Bracket	Vehicle	Vehicle - Marine		Wall					