

DETENTION CABINETS

FOR USE WITH

- FIRE HOSE RACK ASSEMBLY
- PORTABLE FIRE EXTINGUISHER
- 2 1/2" / 6.4 cm FIRE DEPARTMENT VALVE

FUNCTION: Detention Series cabinets accommodate a fire hose rack assembly, fire extinguisher, fire department valve or a combination of these items, based on the model selected. (Refer to capacity column in chart below)

OPTIONAL MATERIALS:

Steel construction: 10 ga., 12 ga., 14 ga. or 16 ga.
Stainless steel: 14 ga. or 16 ga.

REGULARLY FURNISHED:

12 ga. steel box, 12 ga. flat steel door and frame. Heavy-duty continuous hinge with brass pin. All corners mitered and ground smooth. Provision is made for specified security-type lock. All components are powder-coated with an electrostatically-applied, thermally-fused, recoatable white polyester finish. Wall mounting and size of cabinet as selected by model number.

OPTIONAL FINISHES:

Red or any other polyester coating.



DC SERIES

ORDERING INFORMATION


- Select cabinet model number
- Select type of hose rack assembly, fire extinguisher or fire department valve (Refer to capacity column in chart below)
- Select security lock*

SPECIFICATION:


Detention cabinets shall be Model No. _____ as manufactured by Potter Roemer, Santa Ana, CA 800-366-FIRE; containing Model No. _____ fire hose rack assembly, Model No. _____ fire extinguisher or Model No. _____ fire department valve (or a combination of these items based on the cabinet capacity). (Refer to Sections 1000, 2000 and 3000.)

Inlet location shall be on the _____ side, hole diameter shall be _____"; center of hole shall be _____" from top surface of box and _____" from rear surface of box.

*Security locks provided as specified.



RECESSED



SURFACE

For Use As	Model No.	Wall Mounting	Capacity	Outside Box Dimensions			Overall Frame		Wall Opening Required			Shell Z-Z in. cm	ADA
				K in. cm	L in. cm	M in. cm	N in. cm	O in. cm	W ID TH in. cm	H E I G H T in. cm	D E P T H in. cm		
Hose Cabinet	DC-1002	Recessed	100/30.4 m	24 61	30 76.2	5 1/2 14	27 1/4 70.4	33 1/4 85.7	25 63.5	31 78.7	6 15.2	—	Yes
	DC-1052	Surface	Hose Unit	24 61	30 76.2	5 1/2 14	—	—	—	—	—	—	No
Hose and Extinguisher Cabinet	DC-1302	Recessed	100/30.4 m	30 76.2	30 76.2	8 20.3	33 1/4 85.7	33 1/4 85.7	31 78.7	31 78.7	8 1/2 21.5	—	Yes
	DC-1352	Surface	2 1/2 Gal./9.4 l Water Ext.	30 76.2	30 76.2	8 20.3	—	—	—	—	—	—	No
Extinguisher Cabinet	DC-1704	Recessed	10Lb./4.5kg Dry Chemical Ext.	9 22.9	24 61	8 20.3	12 1/4 32.3	27 1/4 70.4	10 25.4	25 63.5	8 1/2 21.5	—	Yes
	DC-1706	Recessed	2 1/2 Gal./9.4 l Water Ext.	12 30.4	27 68.5	8 20.3	15 1/4 40	30 1/4 78.1	13 33	28 71.1	8 1/2 21.6	—	Yes
	DC-1754	Surface	10Lb./4.5kg Dry Chemical Ext.	9 22.9	24 61	8 20.3	—	—	—	—	—	—	No
	DC-1756	Surface	2 1/2 Gal./9.4 l Water Ext.	12 30.4	27 68.5	8 20.3	—	—	—	—	—	—	No
Valve Cabinet	DC-1810	Recessed	2 1/2"/6.4 cm Angle Valve	18 45.7	18 45.7	8 20.3	21 1/4 55.2	21 1/4 55.2	19 48.2	19 48.2	8 1/2 21.6	—	Yes
	DC-1815	Surface	Valve	18 45.7	18 45.7	8 20.3	—	—	—	—	—	—	No
Valve and Extinguisher Cabinet	DC-1870	Recessed	2 1/2"/6.4 cm Angle Valve	14 35.5	40 101.6	8 20.3	17 1/4 45	43 1/4 111.1	15 38.1	41 104.1	8 1/2 21.6	12 30.4	Yes
	DC-1875	Surface	2 1/2 Gal./9.4 l Water Ext.	14 35.5	40 101.6	8 20.3	—	—	—	—	—	12 30.4	No