

# HALOTRON™ I

Halotron™ I clean fire extinguishing agent discharges as a rapidly evaporating liquid, which is non-conductive, non-corrosive, and leaves behind no residue. Halotron™ I is the clean agent market leader with a history of successful real-world protection of valuable assets. From model-scale aircraft to wide-body commercial aircraft, from data centers to pharmaceutical and other industrial plants, the Halotron™ I agent has been used to extinguish the fire, limit damage, and help reduce downtime that can be caused by other agents.

Applications for these extinguishers include: data centers, laboratories, manufacturing plants, general office areas, computer rooms, telecommunication facilities, clean rooms, control rooms, warehouses, military electronics, vehicles including classic autos, boats, engine compartments, aircraft ramps, on-board aircraft, and in facilities that service aircraft and any facility where dry chemical extinguishers could cause unacceptable damage or contamination.

## RUGGED

- 6-Year Manufacturer's Warranty
- Stored Pressure Design
- Dependable Drawn-Steel Cylinders
- Durable High-Gloss Polyester Powder Paint
- All-Metal Valve Construction
- Temperature Range -40°F to 120°F

## USER FRIENDLY

- Maximum Visibility During Discharge
- Large Loop Pull Pin
- No Electrical Conductivity Back to the Operator
- No Thermal or Static Shock
- QR Coded and Bilingual Labels

## ENVIRONMENT

- EPA approved "Clean Agent" for Class A, B and C hazards
- Low GWP (Global Warming Potential) 0.0098, CFC-11=1.0
- Low ODP (Ozone Depletion Potential) -77,100 yr. CO2 time horizon
- Short Atmospheric Lifetime



Aluminum Valve  
A384T  
B385TS  
B386T

## OPTION

- 5 lb. (B386T), 11 lb., and 15½ lb.
- Extinguishers are USCG Approved With Bracket Listed on UL Label
- Chrome Cylinders (See Chart Below)

## CLEAN

- Leaves No Residue



Model 397  
Model 398



B394TS  
FAA Model



### FAA Approved Models Available (See Chart Below)

AGENT TYPE	HALOTRON™ I					
	Anodized Aluminum				Chromed Brass	
DESIGN	Nozzle				Hose & Nozzle	
MODEL NUMBER	A384T	B385TS	B386T	B394TS	397	398
UL & ULC RATING	1B:C	2B:C	5B:C	5B:C	1A:10B:C	2A:10B:C
CAPACITY (LBS.)	1.4	2.5	5	5.5	11	15.5
SHIPPING WT. (LBS.)	3.25	5.25	9.5	10	22.5	27.5
HEIGHT (IN.)	10	15.5	15.25	15	21.88	21.88
WIDTH (IN.)	3.5	6.38	5.75	5.13	9.25	9.25
DEPTH (IN.)	2.63	3	4.25	4.25	6	6
RANGE (INITIAL- FT.)	6-8	6-10	9-15	9-15	9-15	12-18
DISCHARGE TIME (SEC.)	9	9	9	9	9	14
OPTIONAL CHROME CYLINDER	Yes	Yes	Yes			
MINIMUM CONFINED SPACE REQUIREMENTS (CU. FT.)	196	350	700	770	1540	2170
FAA APPROVED MODEL				Yes	Yes	Yes
INCLUDED BRACKET	Vehicle	Vehicle	Vehicle	Aircraft	Wall	Wall

AVAILABLE IN 65/150 LB. WHEELED EXTINGUISHERS

MANUFACTURED AND TESTED TO ANSI/UL STANDARDS  
COMPLIES WITH NFPA 10 STANDARD  
ISO-9001/ ISO-14001 CERTIFIED  
UL LISTED

CONFORMS TO TEST STANDARDS:  
CAN/ULC-S566 - ANSI/UL2129 &  
CAN/ULC-S508 - ANSI/UL711

