

Z-SERIES HIGH PERFORMANCE

Z-Series extinguishers are the ultimate choice in fire extinguishers for high hazard, frequent use, and extreme environment applications. Economical-less initial cost, lower maintenance costs, and greater reliability than cartridge-operated extinguishers. Amerex Z-Series extinguishers are available with a proprietary, zinc-enriched coating that resists corrosion for up to 12 years in severely salt-contaminated environments.

RUGGED

- 12-Year Manufacturer's Warranty
- Zinc-Enriched Coating
- All-Metal Valve Construction
- Gauge Guards are Chrome-Plated Brass
- Protective Rubber Foot Rings
- Superior Range (Vertical & Horizontal)
- High (240 PSI) Operating Pressure
- Temperature Range -65°F to 120°F

AGENTS

- ABC Multi Purpose, Purple K

OPTION

- USCG Approved with Bracket Listed on UL Label
- Hot dip galvanized USCG brackets available

MANUFACTURED AND TESTED TO ANSI/UL STANDARDS

Complies with NFPA 10 Standard ISO-9001 and ISO-14001 Certified UL LISTED

CONFORMS TO TEST STANDARDS:

CAN/ULC-S504 - ANSI/UL299 & CAN/ULC-S508 - ANSI/UL711

USER FRIENDLY

- Wide Grip Allows Clearance for Gloved Hand
- Large Loop Stainless-Steel Pull Pin
- QR Coded and Bilingual Labels

FAST FLOW

- High Flow Rate
- Fast Discharge
- Quicker Knockdown
- More Operator Protection

COMPLIANCE FLOW

- Long Range
- Highest UL Ratings



Fast Flow

790
791
792
723
724
793
794
795
796

Compliance Flow

713
714
715
716
717
718



AVAILABLE IN 125-AND 250-LB. WHEELED EXTINGUISHERS

Affordable and easy to maintain.

AGENT TYPE	ABC DRY CHEMICAL				PURPLE K DRY CHEMICAL				ABC DRY CHEMICAL			PURPLE K DRY CHEMICAL		
PERFORMANCE	FAST FLOW								COMPLIANCE FLOW					
VALVE TYPE	CHROME PLATED BRASS WITH GAUGE GUARD													
DESIGN	HOSE & NOZZLE													
MODEL NUMBER	790	791	792	793	794	795	796	713	714	715	716	717	718	
UL & ULC RATING	2A:40B:C	4A:40B:C	4A:40B:C	40B:C	40B:C	20B:C	40B:C	4A:80B:C	10A:120B:C	10A:160B:C	80B:C	120B:C	160B:C	
CAPACITY (LBS./KG)	13.2/6	20/9	30/13.6	13.2/6	20/9	20/9	30/13.6	13.2/6	20/9	30/13.6	13.2/6	20/9	30/13.6	
SHIPPING WT. (LBS.)	29	40	56	29	40	40	56	29	40	56	29	40	56	
HEIGHT (IN.)	17.5	24.75	26.5	17.5	24.75	24.75	26.5	17.5	24.75	26.5	17.5	24.75	26.5	
WIDTH (IN.)	10.5	10.5	11	10.5	10.5	10.5	11	10.5	10.5	11	10.5	10.5	11	
DEPTH (IN.)	7	7	8	7	7	7	8	7	7	8	7	7	8	
RANGE (INITIAL- FT.)	40-50				40-50				40-50					
DISCHARGE TIME (SEC.)	15	18	21	15	15	10	16	22	30	34	22	29	34	
AVERAGE DISCHARGE RATE (LBS./SEC.)	.94	1.20	1.60	.94	1.44	2.00	1.88	.59	.65	.95	.61	.67	.81	
INCLUDED BRACKET	WALL				WALL				WALL			WALL		

