

# CLEAN AGENT EXTINGUISHERS

## 65 lb. & 150 lb. - Stored Pressure Halotron I™

The Amerex Halotron I™ extinguishers feature the same qualities found in all Amerex products and adds the convenience of a "clean" extinguishing agent. Halotron I™ extinguishing agent has proven itself as the leader in the hunt for an alternative "clean" agent by being the only alternative "clean" agent to obtain FAA approvals for both ramp use (ARFF Vehicle) and on-board an aircraft. Combining the quality of Amerex products with a proven alternative "clean" agent, the Amerex Halotron I™ wheeled extinguishers offer you the best value in the industry.

- ⇒ **EPA approved "Clean Agent" for Class A, B, and C hazards**
- ⇒ **Low GWP (Global Warming Potential)**
- ⇒ **Low ODP (Ozone Depletion Potential)**
- ⇒ **Short Atmospheric Lifetime**
- ⇒ **Maximum visibility during discharge**
- ⇒ **No thermal or static shock**
- ⇒ **No electrical conductivity back to the operator**

### FEATURES:

- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Reflective stripes
- Tow loops
- Stainless Steel Fasteners
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- DOT/TC Cylinders
- Stainless Steel Gauge Guard
- Quick Opening Valves
- Chrome Plated Brass Valve
- Quick Release Discharge Hose
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- 6 Year Warranty

### Available Options:

- 36" x 6" wheels with non-sparking rubber treads

### Test Standards:

CAN/ULC S556 & ANSI/UL 2129  
CAN/ULC S508 & ANSI/UL 711

SPECIFICATIONS	HALOTRON I™		
MODEL NUMBER	B673	B674	B675
AGENT TYPE	CLEAN AGENT		
UL & ULC RATING	4A:80B:C	10A:120B:C	
CAPACITY (LBS. / KG)	65 / 29.5	150 / 68	
SHIPPING WT. (LBS. / KG)	286 / 129.7	512 / 232.2	610 / 276.7
HEIGHT (IN. / CM)	58 / 147.3	64 / 162.6	
WIDTH (IN. / CM)	28 / 71.1	30 / 76.2	37 / 94
DEPTH (IN. / CM)	39 / 99.1	42 / 106.7	43 / 109.2
DISCHARGE TIME (SEC.)	22	38	
DISCHARGE RANGE (FT. / M)	30 - 45 / 9.1 - 13.7		
OPERATING TEMP. (F / C)	-40° to 120° / -40° to +49°		
HOSE LENGTH (FT. / M)	50 / 15.2		
HOSE DIAMETER (IN. / CM)	.75 / 1.9		
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.2		36 X 2.5 / 91.44 X 6.35
USCG APPROVED	YES		

**DESIGNED AND ASSEMBLED IN USA**

