

# STORED PRESSURE

## HIGH PERFORMANCE 125/250 lb. - ABC, REGULAR, PURPLE K Dry Chemical

**HIGH PERFORMANCE** Stored Pressure units are the finest performing dry chemical wheeled fire extinguishers available anywhere! They have a tremendous flow rate, vertical and horizontal range, fire killing ability and operator protection. Wheels are wide footprint 36" X 6".



**250 LB.**

### FEATURES:

- Brass Hose Fittings
- Quick Opening Valves
- Live Swivel on Discharge Valve
- Brass Valve - Chrome Plated
- Heavy Duty Hot Dip Galvanized Steel Cylinders, Carriage, Hose Rack, and Wheels
- Lifting Eyes
- DOT Cylinders (DOT/TC Model 690)
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- Chrome Plated Forged Brass Fill Cap
- Large fill opening
- Stainless Steel Fasteners
- Stainless Steel Gauge Guard
- 12 Year Warranty



**125 LB.**

### Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads

### Test Standards:

CAN/ULC S504 & ANSI/UL 299  
CAN/ULC S508 & ANSI/UL 711

### Available Options:

- Optional 36" x 6" wheels with non-sparking rubber treads

SPECIFICATIONS	DRY CHEMICAL			
MODEL NUMBER	573	574	575	690
AGENT TYPE	ABC	REGULAR	PURPLE K	PURPLE K
UL & ULC RATING	40A:160B:C	160B:C	160B:C	120B:C
CAPACITY (LBS. / KG)	250 / 113.4			125 / 56.7
SHIPPING WT. (LBS. / KG)	775 / 351.3			400 / 181.4
HEIGHT (IN. / CM)	60 / 152.4			53.5 / 135.9
WIDTH (IN. / CM)	37 / 93.98			34 / 86.4
DEPTH (IN. / CM)	44 / 111.76			38.5 / 97.8
DISCHARGE TIME (SEC.)	50	38		30
DISCHARGE RANGE (FT. / M)	60 - 80 / 18.19 - 24.26			50 - 55 / 15.24 - 16.76
OPERATING TEMP. (F / C)	-40° to +120° / -40° to +49°			
HOSE LENGTH (FT. / M)	50 / 15.24			
HOSE DIAMETER (IN. / CM)	1 / 2.54			
WHEELS [STEEL] (IN. / CM)	36 X 6 / 91.44 X 15.24			
USCG APPROVED	YES			

**DESIGNED AND ASSEMBLED IN USA**