

NITROGEN CYLINDER OPERATED

125/150 lb. Regulated Pressure - ABC, REGULAR, PURPLE K Dry Chemical

These 110 ft³ nitrogen cylinder operated models feature a pressure regulator and two wheel options. The older, traditional design allows for adequate pressure to assure a smooth, complete discharge of the dry chemical with pressure reserve for blowing down the discharge hose. Choose either the 16" semi-pneumatic rubber tire or 36" X 2½" steel wheels according to the area to be protected. Easy to transport and operate by one person.



FEATURES:

- Stainless Steel Collars
- Chrome Plated Brass Fill Caps
- Brass Hose Fittings
- Live Swivels on Discharge Valve
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- Lifting Eyes
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- DOT/TC Nitrogen Cylinder with Quick Opening Brass Valve
- Chrome Plated Brass Regulator
- 6 Year Warranty



Available Options:

- Fill Cap with Pressure Indicator

Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- 36" x 6" or 36" x 2½" wheels with non-sparking treads
- Fill Cap with Pressure Indicator

SPECIFICATIONS	125/150 LB. DRY CHEMICAL SEMI-PNEUMATIC WHEELS			125/150 LB. DRY CHEMICAL STEEL WHEELS		
	467	468	469	470	471	472
MODEL NUMBER	467	468	469	470	471	472
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	30A:240B:C	240B:C	320B:C	30A:240B:C	240B:C	320B:C
CAPACITY (LBS. / KG)	125 / 57	150 / 68	125 / 57	125 / 57	150 / 68	125 / 57
SHIPPING WT. (LBS. / KG)	404 / 183	429 / 195	404 / 183	432 / 196	457 / 207	432 / 196
HEIGHT (IN. / CM)	52 / 132					
WIDTH (IN. / CM)	26 / 66			28 / 71		
DEPTH (IN. / CM)	38 / 97			45 / 114		
DISCHARGE TIME (SEC.)	48	53	52	48	53	52
DISCHARGE RANGE (FT. / M)	30 - 40 / 9 - 12					
OPERATING TEMP. (F / C)	-65° to +120° / -54° to +49°					
NITROGEN CYLINDER (CU. FT. / LITER)	110 / 3115					
HOSE LENGTH (FT. / M)	50 / 15.24					
HOSE DIAMETER (IN. / CM)	.75 / 1.90					
WHEELS [SEMI-PNEUMATIC / STEEL] (IN. / CM)	16 X 4 / 40.64 X 10.16			36 X 2.5 / 91.44 X 6.35		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA