

STORED PRESSURE

50, 125/150 lb. Stored Pressure - ABC, REGULAR, PURPLE K Dry Chemical

These commercial stored pressure extinguishers are available in a choice of two sizes and three chemical options. The carriage design on both sizes provides cage type protection for the agent cylinder as well as a well balanced platform for transportation and operation. The narrow width and easy rolling semi-pneumatic rubber tire wheels allow one person movement through narrow aisles, doorways and in confined areas. Chemical and pressure is sealed in the agent cylinder, ready for instant actuation and is always protected from contamination. Stored pressure wheeled extinguishers are less expensive to purchase as well as easier and less costly to maintain and service.



FEATURES:

- Brass Hose Fittings
- Quick Opening Valves
- Live Swivel on Discharge Valve
- Brass Valve - Chrome Plated on 125 lb. & 150 lb. Models
- Lifting Eyes on 125 lb. & 150 lb. Models
- Heavy Duty Steel Cylinder, Carriage, Hose Rack
- DOT/TC Cylinders
- UL/ULC Bilingual (English/Spanish) Nameplates with Bar Code
- Large instruction pictogram
- Chrome Forged Brass Fill Cap on 125 lb. & 150 lb. Models
- Large fill opening on 125 lb. & 150 lb. Models
- Stainless Steel Fasteners
- Stainless Steel Gauge Guard on 125 lb. & 150 lb. Models
- 6 Year Warranty



Test Standards:

CAN/ULC S504 & ANSI/UL 299
CAN/ULC S508 & ANSI/UL 711

Available Options:

- Tow Loop

SPECIFICATIONS	50 LB. DRY CHEMICAL			125/150 LB. DRY CHEMICAL		
MODEL NUMBER	495	496	497	488	489	490
AGENT TYPE	ABC	REGULAR	PURPLE K	ABC	REGULAR	PURPLE K
UL & ULC RATING	20A:160B:C	160B:C	160B:C	30A:240B:C	240B:C	320B:C
CAPACITY (LBS. / KG)	50 / 22.68			125 / 56.7	150 / 68.0	125 / 56.7
SHIPPING WT. (LBS. / KG)	174 / 78.88			344 / 155.95	369 / 167.28	344 / 155.95
HEIGHT (IN. / CM)	46 / 116.84			53.5 / 136.0		
WIDTH (IN. / CM)	21.5 / 54.61			28 / 71.12		
DEPTH (IN. / CM)	24 / 60.96			40 / 101.6		
DISCHARGE TIME (SEC.)	35	33		49	60	52
DISCHARGE RANGE (FT. / M)	25-35 / 7.62 - 10.66			30-40 / 9.1-12.2		
OPERATING TEMP. (F / C)	-40° to +120° / -40° to +49°			-65° to 120° / -54° to +49°		
HOSE LENGTH (FT. / M)	25 / 7.62			50 / 15.2		
HOSE DIAMETER (IN. / CM)	.50 / 1.27			.75 / 1.90		
WHEELS [SEMI-PNEU] (IN. / CM)	12.5 X 3.5 / 31.75 X 8.89			16 X 4 / 40.64 X 10.16		
USCG APPROVED	YES					

DESIGNED AND ASSEMBLED IN USA